

100 srs Single Hung, Horizontal Slider, Triple Slider, Fixed Picture Window

- Our most economical Builder Series Window with most of the standard features of our upper end series
- Spiral balance used on Single Hung. Sash is not removable
- 10 year Limited Warranty on Residential Projects
- Performance ratings from R20 to C40
- Single Weather Stripping
- 1/2" standard glass thickness on Single Hung and Horizontal Sliders. Up to 1" overall glass thickness available on Picture Windows.
- Sloped Sill on Single Hung Windows. Not reliant on weep systems as competitive products
- Tru-Seal , Duraseal spacer used between glass to eliminate seal failure
- Recycled aluminum and powder coating qualifies these products as Green Products
- Standard Mill, White, Sandstone, and Bronze finishes in powder Coat. Custom Finishes only available on custom quote large Quantity Orders.
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

200 srs and 200 srs LC Single Hung, Horizontal Slider, Triple Slider, Fixed Picture Window

- Block and tackle balance used on single hung for easy sash removal
- Limited lifetime warranty on residential projects
- Performance ratings from R25 to C40
- Double weather stripping
- Heavy duty extruded louver blades Lite Commercial Products
- 9/16" standard glass thickness on single hung and horizontal sliders. Up to 1" overall glass thickness available on picture windows
- Sloped sill on single hung windows. Not reliant on weep systems as competitive products
- Tru-Seal, Duraseal spacer used between glass to eliminate seal failure
- Recycled aluminum and powder coating qualifies these products as green products
- Standard white, sandstone, and bronze finishes in powder coat. Custom finishes only available on custom quote large quantity orders
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

400 SRS /Single Hung, Horizontal Slider, Triple Slider, Fixed Picture Window

- Block and tackle balance used on single hung for easy sash removal
- Limited lifetime warranty on residential projects
- Performance ratings from LC35 – C50
- Tubular meeting rail and sloped sill
- Tru-Seal, Duraseal spacer used between glass to eliminate seal failure
- Recycled aluminum and powder coating qualifies these products as green products

- Standard finishes in powder coat colors to meet AAMA's 2603. Custom finishes only available on large quantity orders.
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

400 LC /Single Hung, Horizontal Slider, Fixed Picture Window

- Block and tackle balance used on single hung for easy sash removal
- Standard 1 year warranty on commercial projects, extended warranty available.
- Performance ratings from C40 – C50
- Heavy duty tubular meeting rail and sloped commercial rated sill
- Tru-Seal, Duraseal spacer used between glass to eliminate seal failure
- Recycled aluminum and powder coating qualifies these products as green products
- Standard and custom finishes in powder or liquid and anodized colors to meet AAMA's 2603, 2604, and 2605 guidelines. Custom finishes only available on large quantity orders.
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

400 LC Integral Louver / Single Hung, Horizontal Slider, Fixed Picture Window

- Block and tackle balance used on single hung for easy sash removal
- Standard 1 Year warranty on commercial projects, extended warranty available
- Performance ratings from C40 – C50
- Integral louver system saving on labor and materials since there is no additional opening to frame below the window unit.
- Heavy duty extruded louver blades
- Up to 1" overall glass thickness available on picture windows
- Engineered integral nail fin saving on installation time
- Sloped sill on louver Frame. Not reliant on weep systems as competitive products. Units are randomly water tank tested.
- Heavy duty tubular meeting rail and sloped commercial rated sill
- Tru-Seal, Duraseal spacer used between glass to eliminate seal failure.
- Recycled aluminum and powder coating qualifies these products as green products
- Standard and custom finishes in powder or liquid and anodized colors to meet AAMA's 2603, 2604, and 2605 guidelines. Custom finishes only available on large quantity orders.
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

8400 SRS /Single Hung, Horizontal Slider, Triple Slider, Fixed Picture Window

- High performance [SunShield](#) technology for lasting beauty and durability
- Block and tackle balance used on single hung for easy sash removal
- Limited lifetime warranty on residential projects
- Performance ratings from R25 to C40
- 5/8" overall insulated glass thickness on single hung, horizontal sliders and picture windows.

- Sloped sill on single hung windows. Not reliant on weep systems as competitive products
- Tru-Seal, DuraSeal spacer used between glass to eliminate seal failure
- Vinyl extrusions qualifies these products as green products
- Standard white, tan, and sandstone extrusion colors.
- Custom Exterior frame color option (1 lite or SDL divided lite options only)
- ¾' internal muntins standard.
- 1-1/4 or 7/8 Simulated Divided Lite available
- Fusion welded sash and frame
- Steel reinforced meeting rail for added strength and security
- All virgin vinyl not a re-ground as from other manufacturers
- Tax credit windows have a .30 U-Factor / .22 solar heat gain.
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol

140 SRS /Vinyl Casement, Awning, Fixed

- High performance [SunShield](#) technology for lasting beauty and durability
- Truth heavy duty casement and awning hardware with folding crank handles
- Limited lifetime warranty on residential projects
- Performance ratings from C25 to C50
- 3/4' overall insulated glass thickness
- Primary and secondary weather-strip on sash creating an airtight seal
- Tru-Seal, DuraSeal spacer used between glass to eliminate seal failure
- Vinyl extrusions qualifies these products as green products
- Standard white, tan, and sandstone extrusion Color
- Custom Exterior frame color option (1 lite or SDL divided lite options only)
- ¾' internal muntins standard.
- 1-1/4 or 7/8 Simulated Divided Lite available
- Tested to AAMA standards
- NAMI certified and third party validated in accordance with AAMA protocol
- All virgin vinyl not a re-ground as from other manufacturers
- Windows have a .30 U-Factor / .22 solar heat gain.
- Fusion welded sash and frame